

RAFIX 22 QR, buzzer, round collar, 70 dB



fields of application

- > Measurement-control-regulation
- > Electrical engineering
- > Mechanical and system engineering
- > Vehicle construction



description

Acoustic signal transmitter matching the design of the RAFIX 22 QR actuating elements with round collar shape.

technical data

> general

Bezel color	slate gray
Property of bezel / mushroom	opaque
Collar shape	round
Frequency	2,400 - 3100 Hz
Operating temperature, min.	-25 °C
Operating temperature, max.	70 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	80 °C
Volume 1 m	70 dB
illuminated	No
Tone type	Continuous tone
Packaging	Box
Packaging unit	2 pcs.
net weight	29.3 g
Degree of protection, front side, according to DIN EN 60529	IP65
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
MOQ order	10 pcs.
RoHS compliant	Yes
REACH compliant	Yes

direct links

- > [RAFI eCatalog](#)

> mounting diameters

Outside dimension, length	65.75 mm
Outside dimension, width	48.8 mm
Outside dimension, height	30 mm
Mounting hole	22.3 mm
Mounting depth	56.4 mm

Installation height	9.8 mm
Grid, min.	50 x 30 mm
Collar dimension	ø 29,8 mm
> mechanical data	
Fixing	Threaded ring
Threaded ring torque, max.	1.2 Nm
> electrical data	
Voltage type	DC
Rated operating voltage	24 V
Operating current, max.	25 mA
Power loss	0.60000 W
Maximum connection cross section	1.5 mm ²
Minimum connection cross section	0.25 mm ²

drawings

front panel drawing