


RAFIX 22 FS<sup>+</sup>, illuminated pushbutton, flat bezel, round collar, momentary contact function, frontring black, bezel white

	<b>fields of application</b>	<b>special features</b>
	<ul style="list-style-type: none"><li>➤ Measurement-control-regulation</li><li>➤ Electrical engineering</li><li>➤ Mechanical and system engineering</li><li>➤ Vehicle construction</li><li>➤ Handheld terminals</li><li>➤ Industrial robots</li></ul>	<ul style="list-style-type: none"><li>➤ Illuminated pushbutton, panel illumination with SMT LED</li><li>➤ Low installation depth 9.2 mm (PCB) or 27 mm (QC)</li><li>➤ Special tactile feedback</li><li>➤ Ideal for operation with gloves</li><li>➤ Connection types: printed circuit board connection (PCB) or plug-in connection (QC)</li><li>➤ PCB switching elements minimize assembly errors</li><li>➤ Switching elements with silver contacts (max. 250 V/4 A) or gold contacts (max. 35 V/100 mA)</li><li>➤ The tactile switch adapter allows MICON 5 tactile switches to be used as switching elements</li><li>➤ Design adaptation by different front ring variations</li><li>➤ Degree of protection: IP 65 at the front</li><li>➤ Two collar shapes: round and square</li></ul>



description

RAFIX control devices are defined at RAFI as modular elements, consisting of an actuating element, if necessary a coupling and an individual contact or lighting unit.

Actuating elements (such as pushbuttons, emergency stop actuators, etc.) have the intended tactility, reset and function only when assembled with the appropriate switching elements.

Pushbutton with translucent bezel. In combination with a corresponding switching element, the bezel can be fully illuminated.

technical data

<b>➤ general</b>		<b>direct links</b>
Disassembly possible	no	➤ RAFI eCatalog
Bezel color	white	
Property of bezel / mushroom	translucent	
Front ring color	black	

Collar shape	round
Operating temperature, min.	-25 °C
Operating temperature, max.	70 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	80 °C
illuminated	Yes
Packaging	Box
Packaging unit	10 pcs.
net weight	6.4 g
Operating life	1,000,000 cycles
B10	1,300,000 cycles
Degree of protection, front side, according to DIN EN 60529	IP65
UL Enclosure Type Rating front side	type 1 type 4X indoor
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
Salt-spray resistance according to standard	IEC 60068-2-11
MOQ order	10 pcs.
RoHS compliant	Yes
REACH compliant	Yes
> <b>mounting diameters</b>	
Outside dimension, length	29.8 mm
Outside dimension, width	29.8 mm
Outside dimension, height	18.5 mm
Mounting hole	22.3 mm
Mounting depth	9.2 mm
Installation height	9.85 mm
Grid, min.	30 x 30 mm
Collar dimension	ø 29,8 mm
> <b>mechanical data</b>	
Actuation function	momentary contact function
Operating force, max.	100 N
Operating travel, max.	4 mm
Fixing	Threaded ring
Threaded ring torque, max.	1.2 Nm

## drawings

### Dimensioned drawing



### System drawing



## System drawing



## Mounting hole drawing



acc. to IEC 60947-5-1

## front panel drawing

