

RAFIX 22 FSR, illuminated selector switch, round collar, frontring black, 1 x 90°, shape V, latching, illuminable



fields of application

- › Measurement-control-regulation
- › Mechanical and system engineering
- › Agricultural and forestry machinery
- › Construction machinery

special features

- › Selector switch with illuminated twist grip marking
- › Illumination of the twist grip marking with SMT LED
- › Colored illumination with colored LEDs possible
- › Low installation depth 9.2 mm (PCB) or 27 mm (QC)
- › Connection types: printed circuit board connection (PCB) or plug-in connection (QC)
- › PCB switching elements minimize mounting errors
- › Switching elements with silver contacts (max. 250 V/4 A) or gold contacts (max. 35 V/100 mA)
- › Degree of protection: IP 65 / IP 69K front side



description

RAFIX control devices are defined at RAFI as modular elements, consisting of an actuating element, if necessary a coupling and an individual contact or lighting unit.

Actuating elements (such as pushbuttons, emergency stop actuators, etc.) have the intended tactility, reset and function only when assembled with the appropriate switching elements.

The translucent handle marking can be illuminated if combined with a corresponding switching element.

For colored illumination of the handle marking, please use colored LEDs.

technical data

› general

| | |
|-----------------------------|--------|
| Disassembly possible | no |
| Front ring color | black |
| Collar shape | round |
| Operating temperature, min. | -40 °C |


direct links

- › [RAFI eCatalog](#)

| | |
|--|--|
| Operating temperature, max. | 85 °C |
| Storage temperature, min. | -40 °C |
| Storage temperature, max. | 85 °C |
| illuminated | Yes |
| Packaging | Box |
| Packaging unit | 10 pcs. |
| net weight | 14 g |
| Operating life | 300,000 cycles |
| B10 | 390,000 cycles |
| Degree of protection, front side, according to DIN EN 60529 | IP65 IP69 |
| Degree of protection, front side, according to ISO 20653 | IPx9K |
| UL Enclosure Type Rating front side | type 1 type 4X indoor |
| Environment resistance | IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78 |
| Salt-spray resistance according to standard | IEC 60068-2-11 |
| Impact resistance IK | 06 |
| MOQ order | 10 pcs. |
| RoHS compliant | Yes |
| REACH compliant | Yes |
| > mounting diameters | |
| Outside dimension, length | 31.3 mm |
| Outside dimension, width | 31.3 mm |
| Outside dimension, height | 32.4 mm |
| Mounting hole | 22.3 mm |
| Mounting depth | 9.2 mm |
| Installation height | 23.8 mm |
| Grid, min. | 32 x 32 mm |
| Collar dimension | ø 31,3 mm |
| > mechanical data | |
| Actuation function | latching |
| Operating torque, max. | 2 Nm |
| Rotating angle | 1 x 90°, shape V |
| Fixing | Threaded ring |
| Threaded ring torque, max. | 1.2 Nm |

drawings

System drawing



System drawing

