

## Signal lamp with lamp socket, BA 9s, 18.2 mm, housing, 250 Volt, Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated



### fields of application

- > Measurement-control-regulation
- > Electrical engineering
- > Mechanical and system engineering
- > Signalling systems
- > Model construction



### description

Signal lamps for LEDs or filament/neon lamps with BA 9 s socket, mounting hole diameter 18.2 mm

### technical data

#### > general

Bezel shape	round
illuminated	Yes
Lamp socket	BA9s
Packaging unit	10 pcs.
net weight	11.1 g
Degree of protection, front side, according to DIN EN 60529	IP65
MOQ order	100 pcs.
RoHS compliant	Yes
REACH compliant	Yes

#### direct links

- > [RAFI eCatalog](#)

#### > mounting diameters

Mounting hole	18.2 mm
Mounting depth	47 mm
Installation height	14 mm
Collar dimension	22 mm

#### > mechanical data

Fixing	Threaded ring
Solderability	Yes
Terminal on the rear	Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated

#### > electrical data

Operating voltage of the luminous element, max.	250 V
---	-------

**drawings**

---

**Mounting hole drawing**