

RAFIX 16, lamp socket W2 x 4.6d, quick-connect terminal, for W 2 x 4.6d



fields of application

- › Measurement-control-regulation
- › Electrical engineering
- › Mechanical and system engineering
- › Industrial robots

special features

- › Lamp socket Wedge-Base W 2x4.6d for LED.
- › A notch on the lamp socket indicates the cathode side.
- › Mounting by snapping on or snapping into signal lamp
- › Flat terminals 2.8 x 0.8 mm



description

Lamp socket for snapping in or onto signal lamps.

technical data

› general

| | |
|--|--|
| Color | light gray |
| Operating temperature, min. | -25 °C |
| Operating temperature, max. | 55 °C |
| Storage temperature, min. | -40 °C |
| Storage temperature, max. | 85 °C |
| illuminated | Yes |
| Lamp socket | W 2 x 4.6d |
| Packaging unit | 5 pcs. |
| net weight | 1.8 g |
| Environment resistance | IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78 |
| Shock resistance according to standard IEC 60068-2-27 | 50 g at 11 ms amplitude semi-sinusoidal |
| Vibration-resistance according to standard IEC 60068-2-6 | 10 g at 20 - 500 Hz |
| MOQ order | 10 pcs. |
| RoHS compliant | Yes |
| REACH compliant | Yes |

› mounting diameters

| | |
|---------------------------|---------|
| Outside dimension, length | 15.9 mm |
| Outside dimension, width | 15.9 mm |
| Outside dimension, height | 23.7 mm |
| Mounting depth | 30.5 mm |

direct links

- › [RAFI eCatalog](#)

> mechanical data

| | |
|----------------------|---------------------------------------|
| Fixing | Latching |
| Solderability | No |
| Terminal on the rear | Flat quick-connect terminal 2.8 x 0.8 |

drawings

System drawing