

Pushbutton, 15.2 mm, screw connector, momentary contact function, 1 NO, bezel white



fields of application

- Mechanical and system engineering
- Model construction
- Home technology

special features

Drucktaster opak, nicht beleuchtbar
Einbaudurchmesser 15,2, mm
max. 250 V / 700 mA
Schraub- oder Flachstecker-Anschluss
Befestigungstechnik mit Gewinding
Schutzart IP 40 frontseitig (IP 65 mit Schutzkappe)



description

Pushbutton with mounting hole diameter 15.2 mm

Pushbutton with mounting hole diameter 15.2 mm, screw terminal

technical data

➤ general

| | |
|---|-------------------------------|
| Bezel color | white |
| Property of bezel / mushroom | opaque |
| Collar shape | round |
| Operating temperature, min. | -25 °C |
| Operating temperature, max. | 85 °C |
| Storage temperature, min. | -40 °C |
| Storage temperature, max. | 90 °C |
| illuminated | No |
| Packaging | Box |
| Packaging unit | 100 pcs. |
| net weight | 5 g |
| Operating life | 25,000 cycles |
| B10 | 32,500 cycles |
| Degree of protection, front side, according to DIN EN 60529 | IP40 IP65 with sealing cap |
| MOQ order | 100 pcs. |
| RoHS compliant | Yes |
| REACH compliant | Yes |

direct links

➤ [RAFI eCatalog](#)

➤ mounting diameters

| | |
|--------------------------|---------|
| Outside dimension, width | 19 mm |
| Mounting hole | 15.2 mm |
| Mounting depth | 21.5 mm |
| Installation height | 8.2 mm |

> mechanical data

| | |
|------------------------|----------------------------|
| Actuation function | momentary contact function |
| Operating force, max. | 7.5 N |
| Operating travel, max. | 3 mm |
| Contact function | 1 NO |
| Contact system | Bridge contact |
| Contact material | Silver |
| Fixing | Threaded ring |
| Terminal on the rear | Screw terminal |

> electrical data

| | |
|---------------------|-------|
| Rated voltage, max. | 250 V |
| Rated current, max. | 0.7 A |