

Pushbutton, 9.1 mm, 1NO+1NC, momentary contact function, 1 NC + 1 NO, bezel green



fields of application

- > Mechanical and system engineering
- > Model construction
- > Home technology

special features

- Drucktaster opak, nicht beleuchtbar
- Einbaudurchmesser 9,1, mm
- max. 24 V / 100 mA
- Lötanschluss
- Befestigungstechnik mit Gewinding
- Schutzart IP 40 frontseitig



description

Pushbutton with mounting hole diameter 9.1 mm

Pushbutton with mounting hole diameter 9.1 mm, 1 NC + 1 NO

technical data

> general

| | |
|--|------------------|
| Bezel color | green |
| Property of bezel / mushroom | opaque |
| Collar shape | round |
| Operating temperature, min. | -25 °C |
| Operating temperature, max. | 70 °C |
| Storage temperature, min. | -40 °C |
| Storage temperature, max. | 80 °C |
| illuminated | No |
| Soldering time for manual soldering, max. | 3 sec |
| Soldering temperature for manual soldering | 350 °C |
| Soldering | Manual soldering |
| Packaging | Box |
| Packaging unit | 10 pcs. |
| net weight | 2.2 g |
| Operating life | 200,000 cycles |
| B10 | 260,000 cycles |

direct links

- > RAFI eCatalog

| | |
|---|----------------------------|
| Degree of protection, front side, according to DIN EN 60529 | IP40 |
| MOQ order | 50 pcs. |
| RoHS compliant | Yes |
| REACH compliant | Yes |
| > mounting diameters | |
| Outside dimension, width | 11 mm |
| Mounting hole | 9.1 mm |
| Mounting depth | 25 mm |
| Installation height | 7 mm |
| > mechanical data | |
| Actuation function | momentary contact function |
| Operating force, max. | 5 N |
| Operating force, min. | 5 N |
| Operating travel, max. | 1.5 mm |
| Contact function | 1 NC + 1 NO |
| Contact system | Bridge contact |
| Contact material | Gold |
| Fixing | Threaded ring |
| Solderability | Yes |
| Terminal on the rear | Solder terminal |
| > electrical data | |
| Rated voltage, max. | 24 V |
| Rated current, max. | 0.5 A |