


RAFIX 22 FS<sup>+</sup>, illuminated selector switch, round collar, frontring light gray, 1 x 90°, shape L, latching, illuminable



fields of application

› Measurement-control-regulation

› Electrical engineering

› Mechanical and system engineering

› Vehicle construction

› Handheld terminals

› Industrial robots

special features

› Illumination of the rotary handle marking with SMT LED

› Colored illumination with colored LEDs possible

› Low installation depth 9.2 mm (PCB) or 27 mm (QC)

› Connection types: printed circuit board connection (PCB) or plug-in connection (QC)

› PCB switching elements minimize mounting errors

› Switching elements with silver contacts (max. 250 V/4 A) or gold contacts (max. 35 V/100 mA)

› Design adaptation through different front ring variations

› Degree of protection: IP 65 at the front

› Two collar shapes: round and square



description

RAFIX control devices are defined at RAFI as modular elements, consisting of an actuating element, if necessary a coupling and an individual contact or lighting unit.

Actuating elements (such as pushbuttons, emergency stop actuators, etc.) have the intended tactility, reset and function only when assembled with the appropriate switching elements.

The translucent handle marking can be illuminated if combined with a corresponding switching element.

For colored illumination of the handle marking, please use colored LEDs.

technical data

general		direct links
Disassembly possible	no	› RAFI eCatalog
Front ring color	light gray	
Collar shape	round	
Operating temperature, min.	-25 °C	


Operating temperature, max.	70 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	80 °C
illuminated	Yes
Packaging	Box
Packaging unit	10 pcs.
net weight	10 g
Operating life	300,000 cycles
B10	390,000 cycles
Degree of protection, front side, according to DIN EN 60529	IP65
UL Enclosure Type Rating front side	type 1 type 4X indoor
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
Salt-spray resistance according to standard	IEC 60068-2-11
MOQ order	10 pcs.
RoHS compliant	Yes
REACH compliant	Yes

➤ **mounting diameters**

Outside dimension, length	29.8 mm
Outside dimension, width	29.8 mm
Outside dimension, height	32.4 mm
Mounting hole	22.3 mm
Mounting depth	9.2 mm
Installation height	22.24 mm
Grid, min.	30 x 30 mm
Collar dimension	ø 29,8 mm

➤ **mechanical data**

Actuation function	latching
Operating torque, max.	1.5 Nm
Rotating angle	1 x 90°, shape L
Fixing	Threaded ring
Threaded ring torque, max.	1.2 Nm

**drawings****Dimensioned drawing****System drawing**

## System drawing



## Mounting hole drawing



acc. to IEC 60947-5-1

## front panel drawing

