

Signal lamp with lamp socket, BA 9s, 16.2 mm, IP40, housing, 250 Volt, Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated



- fields of application
- Measurement-control-regulation

➤ Electrical engineering

➤ Mechanical and system engineering

➤ Signalling systems

➤ Model construction

description

Signal lamps for LEDs or filament/neon lamps with BA 9 s socket, mounting hole diameter 16.2 mm

technical data

		direct links
➤ general		
illuminated	Yes	
Lamp socket	BA9s	➤ RAFI eCatalog
Packaging unit	10 pcs.	
net weight	6.9 g	
Degree of protection, front side, according to DIN EN 60529	IP40	
MOQ order	100 pcs.	
RoHS compliant	Yes	
REACH compliant	Yes	
➤ mounting diameters		
Outside dimension, length	20 mm	
Outside dimension, width	20 mm	
Outside dimension, height	60.8 mm	
Mounting hole	16.2 mm	
Mounting depth	45.8 mm	
Installation height	15 mm	
Collar dimension	20 mm	
➤ mechanical data		
Fixing	Threaded ring	
Solderability	Yes	

Terminal on the rear	Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated
> <b>electrical data</b>	
Operating voltage of the luminous element, max.	250 V

## drawings

## Mounting hole drawing

