

Signal lamp with lamp socket, BA 9s, 16.2 mm, IP40, housing, 250 Volt, Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated



fields of application

- > Measurement-control-regulation
- > Electrical engineering
- > Mechanical and system engineering
- > Signalling systems
- > Model construction



description

Signal lamps for LEDs or filament/neon lamps with BA 9 s socket, mounting hole diameter 16.2 mm

technical data

> general

illuminated	Yes
Lamp socket	BA9s
Packaging unit	10 pcs.
net weight	6.9 g
Degree of protection, front side, according to DIN EN 60529	IP40
MOQ order	10 pcs.
RoHS compliant	Yes
REACH compliant	Yes

> mounting diameters

Mounting hole	16.2 mm
Mounting depth	45.8 mm
Installation height	15 mm
Collar dimension	20 mm

> mechanical data

Fixing	Threaded ring
Terminal on the rear	Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated
Solderability	Yes

direct links

- > [RAFI eCatalog](#)

> **electrical data**

Operating voltage of the luminous element, max. 250 V

drawings

Mounting hole drawing