technical data sheet 5.05.511.747/0400



LED, FS technology QC Clip, 12 Volt, yellow





description

> Clip with SMT LED

- > Illumination of illuminated pushbuttons, illuminated selector switches, illuminated emergency stop and illuminated actuators
- > Mounting: snap into switching elements QC and clip carrier for illuminated actuator
- > For better illumination use switching elements with light guide
- > For clear colors we recommend to choose the LED color in the color of the bezel

technical data

>	general		
	Luminous element color	yellow	direct links
	Operating temperature, min.	-40 °C	> RAFI eCatalog
	Operating temperature, max.	85 °C	
	illuminated	Yes	
	Luminous elements	LED	
	Packaging unit	10 pcs.	
	net weight	1 g	
	MOQ order	10 pcs.	
	RoHS compliant	Yes	
	REACH compliant	Yes	
>	mounting diameters		
	Outside dimension, length	18.2 mm	
	Outside dimension, width	7.98 mm	
	Outside dimension, height	17.23 mm	
>	mechanical data		
	Terminal on the rear	Flat quick-connect terminal 2.8 x 0.8	
>	electrical data		
	Operating voltage of the luminous element, min.	9.6 V	
	Operating voltage of the luminous element, max.	14.4 V	
	Voltage type	DC	
	Rated operating voltage	9,6-14,4 V	

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which my change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights. **date**: May 5, 2024 **page**: 1/2

RAFI GmbH & Co. KG

Ravensburger Str. 128-134 88276 Berg / Ravensburg Germany www.rafi-group.com, info.headquarters@rafi-group.com





Power loss

0.28800 W

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which my change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights. **date**: May 5, 2024 **page**: 2/2

RAFI GmbH & Co. KG

Ravensburger Str. 128-134 88276 Berg / Ravensburg Germany www.rafi-group.com, info.headquarters@rafi-group.com