## 5.05.511.747/1200



## LED, FS technology QC Clip, 24 Volt, white





## description

- > Clip with SMT LED
- > Illumination of illuminated pushbuttons, illuminated selector switches, illuminated emergency stop and illuminated actuators
- > Mounting: snap into switching elements QC and clip carrier for illuminated actuator
- > For better illumination use switching elements with light guide
- > For clear colors we recommend to choose the LED color in the color of the bezel

white

## technical data

Luminous element color

>	general

Operating temperature, min. -40 °C
Operating temperature, max. 85 °C
illuminated Yes

Luminous elementsLEDPackaging unit10 pcs.net weight1 gMOQ order10 pcs.RoHS compliantYesREACH compliantYes

> mounting diameters

Outside dimension, length 18.2 mm
Outside dimension, width 7.98 mm
Outside dimension, height 17.23 mm

> mechanical data

Terminal on the rear Flat quick-connect terminal 2.8 x 0.8

> electrical data

Operating voltage of the luminous 19.2 V

element, min.

Operating voltage of the luminous 28.8 V

element, max.

Voltage type DC

Rated operating voltage 19,2-28,8 V

direct links

> RAFI eCatalog

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which my change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights.

date: May 13, 2024 page: 1/2

RAFI GmbH & Co. KG

Ravensburger Str. 128-134 88276 Berg / Ravensburg Germany www.rafi-group.com, info.headquarters@rafi-group.com technical data sheet

5.05.511.747/1200



Power loss 0.05760 W